

Declaration of Performance No. 1125-135-GB

1. Unique identification code of the product-type:

Panic exit devices according to EN 1125:2008

2. Product or product family as required pursuant to Article 11 (4), Regulation (EU) No 305/2011:

Mortise lock GBS 133 in conjunction with Touch Bar EPN 2000 II

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For doors in escape routes, even if these are fire resistance or smoke control doors and in conjunction with a door closer device.

4. Name and contact of the manufacturer as required pursuant to Article 11 (5), Regulation (EU) No 305/2011:


**ECO Schulte GmbH & Co. KG
Iserlohner Landstraße 89
58706 Menden / Germany**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V, Regulation (EU) No 305/2011:

System 1

6. The MPA NRW with the accreditation number No. 432 rated and reviewed in accordance to the specifications of EN 1125:2008 the type test and evaluated the performance in accordance to System 1 and issued the Certificate of constancy of performance 0432-CPR-00099-02.

■ SYSTEMTECHNIK FÜR DIE TÜR



ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89 • D-58706 Menden
Fon +49 2373 9276-0 • Fax +49 2373 9276-40
info@eco-schulte.de • www.eco-schulte.de

7. Declared performance:

Harmonised technical specification: EN 1125:2008

Essential characteristics	Performance
Classification	
7.1 Category of use	Grade 3: High frequency of use
7.2 Durability	Grade 7: 200.000 cycles
7.3 Test door mass	Grade 7: up to 300 kg
7.4 Suitability fire/smoke doors	Grade B: Suitable
7.5 Safety	Grade 1: Suitable
7.6 Corrosion resistance	Grade 3: 96 h [according to EN 1670]
7.7 Security	Grade 2: Suitable
7.8 Projection of device	Grade 2: Standard projection
7.9 Type of device	Type B: Touch Bar operation
7.10 Field of door application	Grade B: Only outside opening single escape door
Type of panic function	Function IV [B] Split spindle hub, constantly active escape door function. It is always possible to use the handle in escape direction to open the door. The handle against escape direction is either permanently engaged or permanently released by turning the key. Against

Control of hazardous substances

The materials used in this product contains no hazardous materials. Also, they give no more into the environment free , as allowed in any European standard or regulation.

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.


This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Tobias Schulte, Managing director ECO Schulte GmbH & Co. KG
(Signatory Name and function in company)

Menden, 01/16/2017



■ SYSTEMTECHNIK FÜR DIE TÜR



ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89 • D-58706 Menden
Fon +49 2373 9276-0 • Fax +49 2373 9276-40
info@eco-schulte.de • www.eco-schulte.de