

## Declaration of Performance No. 1158-18-GB

1. Unique identification code of the product-type:

**Integrated door coordinator devices according to EN 1158:1997/A1:2002/AC:2006**

2. Product or product family as required pursuant to Article 11 (4), Regulation (EU) No 305/2011:

**ECO SRI Size 3-5**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Door coordinator for power-operated double wing swing doors in the mounting variant head mounting hinge side for ECO ETS 64-R, also in connection with fire and smoke protection doors.**

4. Name and contact of the manufacturer as required pursuant to Article 11 (5), Regulation (EU) No 305/2011:


**ECO Schulte GmbH & Co. KG  
Iserlohner Landstraße 89  
58709 Menden / Germany**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V, Regulation (EU) No 305/2011:

**System 1**

6. The MPA NRW with the accreditation number No. 432 rated and reviewed in accordance to the specifications of EN 1158:1997/A1:2002/AC:2006 the type test and evaluated the performance in accordance to System 1 and issued the Certificate of constancy of performance 0432-CPR-00336-01.1.

### ■ SYSTEMTECHNIK FÜR DIE TÜR



**ECO Schulte GmbH & Co. KG**

Iserlohner Landstraße 89 • D-58706 Menden  
Fon +49 2373 9276-0 • Fax +49 2373 9276-40  
info@eco-schulte.de • www.eco-schulte.de

7. Declared performance:

**Harmonised technical specification: EN 1158:1997/A1:2002/AC:2006**

Essential characteristics	Performance
<b>Classification</b>	
4.2 Category of use	Grade 3: For all interior and exterior doors
4.3 Durability	Grade 8: 500.000 cycles
4.4 Door coordinator size	Size 3-5: Recommended max. door width: 1250 mm
4.5 Suitability fire/smoke doors	Grade 1: Suitable
4.6 Safety	Grade 1: Suitable
4.7 Corrosion resistance	Grade 0: No defined corrosion resistance

**Control of hazardous substances**

The materials used in this product contains no hazardous materials. Also, they give no more into the environment free , as allowed in any European standard or regulation.

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Tobias Schulte, Managing director ECO Schulte GmbH & Co. KG  
(Signatory Name and function in company)

Menden, 05/28/2020



■ SYSTEMTECHNIK FÜR DIE TÜR



**ECO Schulte GmbH & Co. KG**

Iserlohner Landstraße 89 • D-58706 Menden  
Fon +49 2373 9276-0 • Fax +49 2373 9276-40  
info@eco-schulte.de • www.eco-schulte.de