



ECO  SGL Click

Rosette set with quick assembly



1... 2... 3... **Click**



STEP 1 Insert the handle with the pre-assembled square spindle into the lock follower.



STEP 2 Slide the plastic base rosette over the square spindle and screw in place. A red centring aid is included in the set.



STEP 3 Slide the cover rosette on. Push the handle onto the spindle and **click** into place. Tighten the set screw (grub screw), job done!



Product characteristics at a glance

- New packaging for simple removal
- Packed as sets
- Can be used for **DIN left / DIN right**
- Restoring spring
- All current handle types available
- Maintenance-free handle bearing
- Fixable bearing
- 45° operating angle
- ECO **Click** quick assembly
- **EN 1906**, user class 3 certified
- Pre-assembled, fixed sleeve nuts
- Sturdy M5 screw attachment
- High-strength pin connection (grooved square spindle)
- Standard door thickness 38-45mm*
- 55 mm rosette diameter

SGL **Click** is available for all handle models as well as for all knob/handle and toilet door sets.

Watch the SGL **Click** assembly video here.



3	7	-	0	1	4	0	A
---	---	---	---	---	---	---	---

EN 1906

* Further door thicknesses on request.

ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89

D-58706 Menden

Phone +49 2373 9276 - 0

Fax +49 2373 9276 - 40

info@eco-schulte.de

www.eco-schulte.de

Your company logo

■ SYSTEM TECHNOLOGY FOR THE DOOR

