





ECO D-330 Plate handle

Product information



■ SYSTEM TECHNOLOGY FOR THE DOOR





Product characteristics

Tested acc. to	EN 1906
With 9 mm spindle acc. to DIN 18273 fire protection tested	F
Lever form for escape doors and emergency exits	EN 179
Restoring spring	-
Fixable bearing	■
Steel base with positioning studs	■
Concealed through-screw technology	■
DIN left / right	■

Classification key EN 1906

4	7	-	B1	1	4	0	U
---	---	---	----	---	---	---	---

■ Yes - No ■ Option



Material:



Bearing technology:




PRODUCT FAMILY D-300

Standard handle




D-310 D-330

Long- / short plate handle




D-330 D-330

Oval rose handle



D-310 D-315 D-335

Security handle




D-310 D-315

Window handle



F-310

D-330 Long plate (L)




D-330 Long plate (L) with OKL – ball bearing technology

The lever is clenched inside the inner ring of the ball-bearing. The outer ring of the ball-bearing is fixed into the base construction. This connection guarantees an additional lasting of the lever sets on the door leaves and is known for high capacity in axial and radial direction.

Utilization category class 4

PZ 92 hole on request, Positioning studs Ø 8 x 5 mm







OKL – LONG PLATE HANDLE (L)




EN 1906 EN 179  F

F = 4 7 - B1 1 4 0 U



		Sets	
			
F	21 mm 9 mm	3k6805.46	3k6815.46





Finish: Stainless steel satin brushed



EN 1906 EN 179  F


F = 4 7 - D1 1 4 0 U



		Sets	
			
F	22 mm 9 mm	3k7805.30	3k7815.30

Finish: Aluminium anodized F1, further colours on request


D-330 Long plate (L)



D-330 Long plate (L) with OGL – friction bearing technology

Maintenance-free metal friction bearing. Fixable bearing. DIN left / DIN right useable. Steel base with positioning studs. Concealed, continuous screw connection.

Utilization category class 4
PZ 92 hole on request. Positioning studs Ø 8 x 5 mm







OGL – LONG PLATE HANDLE (L)



EN 1906 EN 179  F

F = 4 7 - B1 1 4 0 U



		Sets	
			
F	22 mm 9 mm	3g6805.46	3g6815.46





Finish: Stainless steel satin brushed



EN 1906 EN 179  F

F = 4 7 - D1 1 4 0 U



		Sets	
			
F	22 mm 9 mm	3g7805.30	3g7815.30

Finish: Aluminium anodized F1, further colours on request


D-330 Short plate (K)




D-330 Short plate (K) with OGL – friction bearing technology

Lever guidance consists of a closed, maintenance-free friction bearing with self-lubricating plastic. Fixable bearing. DIN left / DIN right useable. Steel base with positioning studs. Concealed, continuous screw connection.

Utilization category class 4. Positioning studs $\varnothing 8 \times 5$ mm.



OGL – SHORT PLATE HANDLE (K)




EN 1906 EN 179 F

F = 4 7 - B1 1 4 0 U



	Ø	▧	Sets						Passive leaf sets	
S	21 mm	8 mm		106805.46	106800.46	106810.46	106860.46	106820.46		
F	21 mm	9 mm	306881.46	306800.46		306860.46	306863.46		306825.46	306818.46 306817.46
	21 mm	9 mm		306850.46						

Finish: Stainless steel satin brushed. PVD and polished on request



EN 1906 EN 179 F

F = 4 7 - D1 1 4 0 U



	Ø	▧	Sets						Passive leaf sets	
S	22 mm	8 mm			107205.30	107200.30	107210.30	107220.30		
F	22 mm	9 mm	307881.30	307883.30	307800.30		307860.30		307804.30	307819.30 307817.30
	22 mm	9 mm			307850.30					

Finish: Aluminium anodized F1, further colours on request

ECO Schulte GmbH & Co. KG
Iserlohner Landstraße 89
D - 58706 Menden

Telefon: +49 2373/9276-0
Fax: +49 2373/9276-40

info@eco-schulte.de
www.eco-schulte.de

© ECO Schulte GmbH & Co. KG - Änderungen vorbehalten
© ECO Schulte GmbH & Co. KG - Subject to change