

Declaration of Performance No. 179-1251-GB

1. Unique identification code of the product-type:

Emergency exit devices according to EN 179:2008

2. Product or product family as required pursuant to Article 11 (4), Regulation (EU) No 305/2011:

Mortise lock GBS 968 RZ in conjunction with handle sets of Wilhelm May GmbH with the coding EN 179

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Emergency exit devices operated by a lever handle for doors in escape routes, even if these are fire resistance or smoke control doors and in conjunction with a door closer device.

4.1 Name and contact of the manufacturer as required pursuant to Article 11 (5), Regulation (EU) No 305/2011:

**ECO Schulte GmbH & Co. KG
Iserlohner Landstraße 89
58706 Menden / Germany**

4.2 Name and contact of the handle set manufacturer as required pursuant to Article 11 (5), Regulation (EU) No 305/2011:


**Wilhelm May GmbH
Gießereistraße 3
42551 Velbert / Germany**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V, Regulation (EU) No 305/2011:

System 1

6. The MPA NRW with the accreditation number No. 432 rated and reviewed in accordance to the specifications of EN 179:2008 the type test and evaluated the performance in accordance to System 1 and issued the Certificate of constancy of performance 0432-CPR-00005-02.3.

■ SYSTEMTECHNIK FÜR DIE TÜR



ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89 • D-58706 Menden
Fon +49 2373 9276-0 • Fax +49 2373 9276-40
info@eco-schulte.de • www.eco-schulte.de

7. Declared performance:

Harmonised technical specification: EN 179:2008

Essential characteristics	Performance
Classification	
7.1 Category of use	Grade 3: High frequency of use
7.2 Durability	Grade 7: 200.000 cycles
7.3 Test door mass	Grade 7: up to 400 kg
7.4 Suitability fire/smoke doors	Grade B: Suitable
7.5 Safety	Grade 1: Suitable
7.6 Corrosion resistance	Grade 3: 96 h [according to EN 1670]
7.7 Security	Grade 5: 5000 N (highest class)
7.8 Projection of operating element	Grade 2: Standard projection
7.9 Type of operation	Type A: Lever handle
7.10 Field of door application	Grade B: Only outside opening single escape door
Type of panic function	Function II Split spindle hub, constantly active escape door function. It is always possible to use the handle in escape direction to open the door. The handle against escape direction, respectively the split hub in escape direction, will be electronically engaged

Control of hazardous substances

The materials used in this product contains no hazardous materials. Also, they give no more into the environment free, as allowed in any European standard or regulation.

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.1.

Tobias Schulte, Managing director ECO Schulte GmbH & Co. KG
(Signatory Name and function in company)

Menden, 05/14/2020



■ SYSTEMTECHNIK FÜR DIE TÜR



ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89 • D-58706 Menden
Fon +49 2373 9276-0 • Fax +49 2373 9276-40
info@eco-schulte.de • www.eco-schulte.de